



大きさ	a	b1	b2		E	H
			1 POINT	2 POINTS		
75	20	49	65	71	90	107
100	21	53	67	75	115	146.5

JIS10kgf/cm²

SIZE	10A	15A	20A	25A	40A	50A
A	31	36	41	41	52	52
C	65	70	75	90	105	120
D	90	95	100	125	140	155
t	15	15	20	20	20	20
h	15	15	15	19	19	19

接点容量
CAPACITY : AC100V 0.5A MAX. at R

⑥	Diaphragm ダイヤフラム	PTFE				
⑤	Lower Flange 下フランジ	PVC. HT-PVC. PP			Order No. 貴注番	
④	Upper Flange 上フランジ	Steel Cr Plating 鉄クロムメッキ . SUS304			Scale Range 目盛範囲	MP a
③	Socket 接続部	Brass . SUS			Quantity 台数	
②	Case ケース	Plastic 樹脂	Black 黒色		Flange Size フランジ呼び径	
①	Cover カバー	Plastic 樹脂	Black 黒色		Remarks 備考	
No.	Name 部品名	Material 材質	Finish 処理			
MATERIAL 材質	DESIGNED FOR Diaphragm-Seal Type 品 Pressure Gauge With 1 or 2 Contact Points 名 PK コンタクト1・2接点付隔膜式圧力計			PLATES NO. 品番	MODELS TO BE USED QTY.	
FINISH 処理	MODEL AND SIZE 型名 PK-8F A φ75. φ100			DATE 2009. 03. 11	CHKD. KOTSUNA	
SCALE 尺度	TOLERANCE 公差	TITLE 図名 Outside Drawing 外形図		DRWN. TANABE	APPD. OHANA	
Free	±			DRWG NO. 図番	CD08AUOY000C PK8F2-002	

