



SYM.	DATE	DESCRIPTION	REV. BY
	2021. 06. 28	A, B, Cマイクروسイッチ仕様変更の為、書換	HONDA

d	f	D	F
1/4	16	26	73
3/8	18	26	75
1/2	20	26	77
3/4	22	29	79
1	25	35	90

接点容量 CONTACT CAPACITY			
	電圧	AC定格電流	DC定格電流
A	30V	—	1A
	125V	7.5A	—
	250V	7.5A	—
B1	30V	—	3A
	125V	7.5A	0.4A
	250V	7.5A	0.2A
C1	30V	—	3A
	125V	7.5A	0.5A
	250V	7.5A	0.25A
D	30V	—	7.5A
	125V	7.5A	7.5A
	250V	7.5A	3A

④	Diaphragm ダイヤフラム	SUS316L . PTFE					
③	Lower Box 下箱	SUS304 . SUS316		Order No. 貴注番			
②	Upper Box 上箱	Steel Cr Plating 鉄クロムメッキ . SUS304		Scale Range 目盛範囲			MP a
①	Case ケース	A D C	Munsell マンセル 7.5BG7/2	Quantity 台数			
No.	Name 部品名	Material 材質	Finish 処理	Remarks 備考			
MATERIAL 材質	DESIGNED FOR 品名 Diaphragm-Seal Type Pressure Switch 隔膜式圧力スイッチ			PLATES NO. 品番	MODELS TO BE USED		
FINISH 処理	MODEL AND SIZE 型名 PK-1 DK-F8			DATE	2021. 06. 28	CHKD.	KONTANI
SCALE 尺度	TOLERANCE 公差	TITLE 図名 Outside Drawing 外形図		DRWN.	HONDA	APPD.	TANABE
Free	±			DRWG NO. 図番	DKF8-PK1-001		

